

MOREY'S AIR TOOL OIL



MOREY'S AIR TOOL OIL is especially engineered for the care of all piston-type and rotary air tools. It prevents rust formation during storage, provides positive lubrication for longer tool life and smoother starting. Ensures maximum output, and top performance by dissolving the gums and sludge that rob tools of speed and power.

Helps keep air tools in peak condition. Ensures adequate lubrication at start up. Practical implementations of Air Tool oil are oil mist and in-line lubrication systems where accelerated oxidation due to high and low temperatures are controlled by this product.

The ability to reduce formation deposits as well as the excellent water separation properties enable these systems to operate for long trouble free periods, while improving efficiency, power and performance, with reduced down time and maintenance cost.

Typical Uses:

- For small high speed air operated drills at low atmospheric temperatures.

Features:

- Excellent extreme pressure properties to protect tools from seizure.
- Good adherence to wet surfaces.
- Good rust prevention properties

Typical Properties:

Grade ISO	32
Specific Gravity @ 15°C	.8833
Viscosity (KIN cSt) @ 40°C	43.10
Viscosity (KIN cSt) @ 100°C	8.24
Flash Point (COC) °C	>196
Pour Point °C	-18

Values shown here are typical and may vary.

MOREY OIL SOUTH PACIFIC LTD
ISO 9001-14001 CERTIFIED SUPPLIER
www.moreyoil.co.nz

07/02/2011